


# PRODUCT DATASHEET

## PANEL VAL 600 40 W 6500 K WT

PANEL VALUE 600 | Square recessed panel luminaires, 600 x 600 mm



---

### AREAS OF APPLICATION

- Direct replacement for luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators
- Suitable for recessed ceiling systems with grid size of 600 x 600 mm

---

### PRODUCT BENEFITS

- Value for money luminaire
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 100 lm/W
- External driver for extended flexibility and easy installation
- Further variants with DALI ECG available

---

### PRODUCT FEATURES

- Lifetime (L70/B50): up to 50,000 h (at 25 °C)
- Extruded aluminum frame
- Polystyrene diffuser



**TECHNICAL DATA**

Electrical data

Nominal wattage	40.00 W
Operating mode	External LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Power factor $\lambda$	>0.90
Inrush current	26.0 A
Total harmonic distortion	$\leq 20 \%$
Inrush current time $T_{h50}$	90 $\mu$ s


Luminaire control gear data

ECG - Output voltage	30...42 V
Output current	1000 mA
ECG - Output ripple current	<5 %
Low flicker	Yes
Max. no. of lum. on circuit break. B16 A	22
Max. no. of lum. on circuit break. C10 A	19
Max. no. of lum. on circuit break. C16 A	30

Photometrical data

Color temperature	6500 K
Color rendering index Ra	>80
Light color (designation)	Cool Daylight
Luminous flux	3600 lm
Luminous efficacy	90 lm/W
Standard deviation of color matching	<5 sdc <sub>m</sub>

Dimensions & weight



<b>Length</b>	595.0 mm
<b>Width</b>	595.0 mm
<b>Height</b>	9.0 mm
<b>Product weight</b>	1990.00 g
<b>Mounting width</b>	575 mm
<b>Mounting length</b>	575 mm

### Colors & materials

<b>Product color</b>	White
<b>Housing color</b>	White
<b>Body material</b>	Aluminum
<b>Light emitting surface material</b>	Polystyrene

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-10...+45 °C
----------------------------------	--------------

### Lifespan

<b>Number of switching cycles</b>	30000
<b>Lifespan L70/B50 at 25 °C</b>	50000 h
<b>Lifespan L80/B10 at 25 °C</b>	40000 h
<b>Lifespan L90/B10 at 25 °C</b>	30000 h

### Additional product data

<b>Mounting type</b>	Recessed/Suspended/Surface
<b>Mounting location</b>	Ceiling / Wall



### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Screw terminal, 2-Pole (L,N)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Type of protection</b>	IP20
<b>Protection class</b>	II
<b>Protection class IK (shock resistance)</b>	IK03
<b>Glow Wire Test according to IEC 695-2-1</b>	650 °C
<b>Photobiological safety group EN62778</b>	RG 1
<b>Standards</b>	CE/CB

Light Distribution



LDC typ cone

LDC typ polar

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- External control gear included
- Security brackets included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075066625	Folding carton box 1	50 mm x 665 mm x 640 mm	2845.00 g	21.28 dm <sup>3</sup>
4058075066632	Shipping carton box 4	657 mm x 211 mm x 688 mm	12420.00 g	95.38 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see  
 ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.